




Socket outlets with earthing pin

- for 4-hole screw fitting

Socket outlets with earthing pin and screw terminals

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with hinged cover and imprint "IP44" and contact protection box.

Socket outlet with earthing pin



- screw terminals

- 2pole + earth



Rated voltage 250 V~
Rated current 16 A

Connection terminals according to IEC 60884-1

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Design	Order no.	PU
brown matt	8 6185 25 01	200
anthracite matt	8 6185 25 05	200
polar white matt	8 6185 25 02	200
black matt	8 6185 05	200
brown matt	9 6185 25 01	10
anthracite matt	9 6185 25 05	10
grey matt	9 6185 25 06	10
polar white matt	9 6185 25 02	10
black matt	9 6185 05	10



Socket outlet with earthing pin



- enhanced contact protection
- screw terminals

- 2pole + earth



Rated voltage 250 V~
Rated current 16 A

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Suitable for	Order no.	Page
Contact protection box Ø 45 mm	9 1820 ..	63
Contact protection box Ø 49 mm	9 188 ..	63
Contact protection box 2gang	9 191 ..	63
Contact protection box 3gang	9 1933	64
Optional		
Sealing for IP44 applications	9 1853	78
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Design	Order no.	PU
anthracite matt	8 6195 25 05	200
grey matt	8 6195 25 06	200
polar white matt	8 6195 25 02	200
black matt	8 6195 05	200
brown matt	9 6195 25 01	10
anthracite matt	9 6195 25 05	10
grey matt	9 6195 25 06	10
polar white matt	9 6195 25 02	10
black matt	9 6195 05	10



Socket outlets with earthing pin and insulation-piercing terminals

- New: Insulation-piercing terminals (IPT) for quick and easy connection with the joining tool, order no. 8 1726 25 81
- VDE approval
- Up to 2 flexible conductors with a cross section of 2.5 mm² can be connected for each IPT contact; wires do not have to be stripped in advance.
- Enables multiple socket outlets to be looped through without breaking the conductors.
- IPT contacts made from copper alloy, tin-plated
- thermoplastic centre plates and bases
- Base with snap-on safety cap

Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853 01) and frame with hinged cover and imprint "IP44".



Socket outlet with earthing pin

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
Conductor cross-section (flexible)	2.5 mm ²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- 2pole + earth

Suitable for Optional	Order no.	Page
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Design	Order no.	PU
anthracite matt	★ 8 6301 25 05	200
polar white matt	★ 8 6301 25 02	200
red matt	★ 8 6301 25 07	200
green matt	★ 8 6301 25 03	200
orange matt	★ 8 6301 25 04	200



Socket outlet with earthing pin and control LED

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
LED current	1 mA
Conductor cross-section (flexible)	2.5 mm ²

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- with green control LED as function light
- 2pole + earth

Suitable for Optional	Order no.	Page
Frame with hinged cover and imprint "IP44"		upon request
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79

Design	Order no.	PU
anthracite matt	★ 8 6301 25 15	200
grey matt	★ 8 6301 25 16	200
polar white matt	★ 8 6301 25 12	200
black matt	★ 8 6301 25 18	200
red matt	★ 8 6301 25 17	200
green matt	★ 8 6301 25 13	200
orange matt	★ 8 6301 25 14	200





Socket outlet with earthing pin 45°

▶ 212

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
Conductor cross-section (flexible)	2.5 mm ²

- for diagonal installation
- 2pole + earth

Suitable for	Order no.	Page
Optional		
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79
Frame with hinged cover and imprint "IP44"	8 1828 ..	77

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Design	Order no.	PU
anthracite matt	★ 8 6351 25 05	200
polar white matt	★ 8 6351 25 02	200
red matt	★ 8 6351 25 07	200
green matt	★ 8 6351 25 03	200
orange matt	★ 8 6351 25 04	200



Socket outlet with earthing pin 45° and control LED

▶ 212

- enhanced contact protection
- insulation-piercing terminals



Rated voltage	250 V~
Rated current	16 A
LED current	1 mA
Conductor cross-section (flexible)	2.5 mm ²

- with green control LED as function light
- for diagonal installation
- 2pole + earth

Suitable for	Order no.	Page
Optional		
Frame with hinged cover and imprint "IP44"		upon request
Sealing IP44 for socket outlets with insulation displacement contacts	9 1853 01	79

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

Design	Order no.	PU
anthracite matt	★ 8 6351 25 15	200
grey matt	★ 8 6351 25 16	200
polar white matt	★ 8 6351 25 12	200
black matt	★ 8 6351 25 18	200
red matt	★ 8 6351 25 17	200
green matt	★ 8 6351 25 13	200
orange matt	★ 8 6351 25 14	200

