










Guida supporto in acciaio, con zincatura elettrolitica e passivazione
 Steel mounting rail, galvanic zinc plating and passivation
 Tragschiene aus Stahl, mit galvanische Verzinkung und Passivierung
 Profilé asymétrique en acier, zingage galvanique avec passivation

Norme - Standards - Normen - Normes
 EN 60715


	Giallo - Yellow Gelb - Jaune	Bianco - White Weiss/Blau - Blanc		
	1 M			
2 M			40 M	0,730 / M
3 M			30 M	0,730 / M

TS 32






	Giallo - Yellow Gelb - Jaune	Bianco - White Weiss/Blau - Blanc		
	1 M			
2 M			40 M	0,690 / M
3 M			30 M	0,690 / M

TS 32/F5A







Guida supporto in acciaio, zincato a caldo con processo Sendzimir
 Steel mounting rail, hot-dip galvanized using the Sendzimir process
 Tragschiene aus Stahl, sendzimir verzinkt (Bandverzinkt)
 Profilé asymétrique en acier, galvanisation à chaud selon le procédé Sendzimir

Norme · Standards · Normen · Normes
 EN 60715


			
1 M		20 M	0,690 / M
2 M		40 M	0,690 / M
3 M		30 M	0,690 / M

TS 32/F5 Sz.



			
1 M		20 M	0,690 / M
2 M		40 M	0,690 / M
3 M		30 M	0,690 / M

TS 32/F6 Sz.




Guida supporto in acciaio, zincato a caldo con processo Sendzimir
 Steel mounting rail, hot-dip galvanized using the Sendzimir process
 Tragschiene aus Stahl, sendzimir verzinkt (Bandverzinkt)
 Profilé asymétrique en acier, galvanisation à chaud selon le procédé Sendzimir

Norme · Standards · Normen · Normes
 EN 60715


1 M	20 M 0,730 / M
2 M	40 M 0,730 / M
3 M	30 M 0,730 / M

TS 32/Sz.



1 M	20 M 0,690 / M
2 M	40 M 0,690 / M
3 M	30 M 0,690 / M

TS 32/F5A Sz.






Guida supporto in alluminio
 Aluminium mounting rail
 Tragschiene aus Aluminium
 Profilé en aluminium

Norme - Standards - Normen - Normes
 EN 60715


	 
2 M	40 M 0,240 / M

TS 32 ALU



	 
2 M	40 M 0,122 / M

TS 35 ALU



Esecuzione con riferimento: Manufacture with reference:
 Durchführung laut: Exécution avec référence:
 Norme - Standards - Normen - Normes
 EN 60715

	 
2 M	20 M 0,343 / M

TS 35/C ALU

