

# MC 25

STRIPPER-  
CRIMPER



# MC 25 | STRIPPER- CRIMPER



## Abisolieren und Crimpen in einem Arbeitsschritt

Der **MC 25** verarbeitet isolierte Aderendhülsen in Bandform. Zur Standard-Ausstattung des elektrischen Abisolier- und Crimpautomats zählen Wechselwerkzeuge mit einem Querschnitt von 0.5-2.5 mm<sup>2</sup>.

Die Crimpeinsätze lassen sich mit wenigen Handgriffen ohne Hilfsmittel sicher wechseln. Optional bietet das Erweiterungs-Kit die Möglichkeit, 0.25-0.34 mm<sup>2</sup>-Leiter zu verarbeiten.

- ☞ Mobil einsetzbar
- ☞ Kompakte Bauweise
- ☞ Schneller Querschnittswechsel
- ☞ Hohe Zuverlässigkeit
- ☞ Einfache Handhabung
- ☞ Geräuscharmer Betrieb

## Stripping and crimping in one work step

The **MC 25** processes insulated wire-end ferrules in strips. As standard, this electrical stripping and crimping machine includes interchangeable tools with a cross-section of 0.5-2.5 mm<sup>2</sup>.

The crimping dies can be easily and safely changed without tools. Optionally, the expansion kit offers the possibility to process 0.25-0.34 mm<sup>2</sup> conductors.

- ☞ Suitable for mobile use
- ☞ Compact design
- ☞ Cross-section can be quickly changed
- ☞ High level of reliability
- ☞ Easy to operate
- ☞ Quiet operation



### TECHNISCHE DATEN:

Querschnitt:	0.5-2.5 mm <sup>2</sup> (AWG 20-14)
Optional:	0.25-0.34 mm <sup>2</sup> (AWG 24-22)
Crimplänge:	8 mm
Zykluszeit:	1.5 sec
Stückzähler:	6-stellig
Netzanschluss:	230 VAC/50 Hz
Stromverbrauch:	160 VA
Maße (BxHxT):	165 x 270 x 320 mm
Gewicht:	12 kg

### TECHNICAL DATA:

Cross-section:	0.5-2.5 mm <sup>2</sup> (AWG 20-14)
Optional:	0.25-0.34 mm <sup>2</sup> (AWG 24-22)
Crimping length:	8 mm
Pressing time:	1.5 sec
Counter:	6-digit
Power supply:	120 VAC/60 Hz
Power consumption:	160 VA
Dimensions (WxHxD):	6.5 x 10.6 x 12.6"
Weight:	26 lbs.

