




Non-insulated Silver Brazed Terminals



General features

✓ Material: tin-plated electrolytic copper.



W

F

Ø i



mm ²	Item code	Part No.	Packing	Ø mm	W	F	Ø i	Type of dies
0.5 - 1.5	7385300	BY1M32D	100	3	6	11	1.6	Tool MB524
	7385301	BY1M37D	100	3.5	6	11	1.6	
	7385302	BY1M43D	100	4	8	12	1.6	
	7385303	BY1M53D	100	5	8	12.5	1.6	
	7385304	BY1M65D	100	6	11	15	1.6	
1.5 - 2.5	7385306	BY25M32D	100	3	6	11	2.3	Tool MB524
	7385307	BY25M37D	100	3.5	6	11	2.3	
	7385308	BY25M43D	100	4	8	12	2.3	
	7385309	BY25M53D	100	5	8	13.5	2.3	
	7385310	BY25M65D	100	6	10	14	2.3	
2.5 - 6	7385311	BY25M84D	100	8	11	16	2.3	Tool MB526
	7385313	BY6M43D	100	4	8	14	3.6	
	7385314	BY6M53D	100	5	10	15	3.6	
	7385315	BY6M65D	100	6	11	16	3.6	
	7385316	BY6M84D	100	8	14	19	3.6	
10	7385317	BY6M105D	100	10	18	21	3.6	..DMB10
	7385318	BY5-10	100	5	10	16	4.5	
	7385319	BY6-10	100	6	11	17	4.5	
	7385320	BY8-10	100	8	14	20	4.5	
	7385321	BY10-10	100	10	18	21	4.5	
16	7385322	BY12-10	100	12	22	23	4.5	..DMB16
	7385323	BY5-16	100	5	11	20	5.8	
	7385324	BY6-16	100	6	11	20	5.8	
	7385325	BY8-16	100	8	14	22	5.8	
	7385326	BY10-16	100	10	18	24	5.8	
25	7385327	BY12-16	100	12	22	26	5.8	..DMB25
	7385328	BY6-25	100	6	12	25	7.5	
	7385329	BY8-25	100	8	16	25	7.5	
	7385330	BY10-25	100	10	18	26	7.5	
	7385331	BY12-25	100	12	22	31	7.5	
35	7385332	BY6-35	100	6	15	26	9.4	..DMB35
	7385333	BY8-35	100	8	16	26	9.4	
	7385334	BY10-35	100	10	18	27	9.4	
	7385335	BY12-35	100	12	22	31	9.4	
	7385336	BY16-35	100	16	28	32	9.4	
50	7385337	BY6-50	50	6	18	34	11	..DMB50
	7385338	BY8-50	50	8	18	34	11	
	7385339	BY10-50	50	10	18	34	11	
	7385340	BY12-50	50	12	22	36	11	
	7385341	BY16-50	50	16	28	40	11	



Nominal section (mm²)



Packing



Stud size



Type of dies


Unless otherwise stated, all dimensions are in millimeters.



Non-insulated Silver Brazed Terminals

General features

✓ Material: tin-plated electrolytic copper.



mm ²	Item code	Part No.	Packing	Stud size Ø mm	W	F	Ø i	Type of dies
70	7385343	BY8-70	50	8	22	38	13	..DMB70
	7385344	BY10-70	50	10	22	38	13	
	7385345	BY12-70	50	12	22	38	13	
	7385346	BY16-70	50	16	28	42	13	
95	7385348	BY10-95	25	10	24	42	15	..DMB95
	7385349	BY12-95	25	12	24	42	15	
	7385350	BY16-95	25	16	28	44	15	
120	7385352	BY10-120	25	10	24	44	16.4	C6DMB120
	7385353	BY12-120	25	12	24	44	16.4	
	7385354	BY16-120	25	16	28	48	16.4	
150	7385355	BY10-150	25	10	30	50	19	upon request
	7385356	BY12-150	25	12	30	50	19	
	7385357	BY16-150	25	16	30	50	19	
185	7385359	BY12-185	25	12	36	50	21	upon request
	7385360	BY16-185	25	16	36	50	21	
240	7385362	BY12-240	10	12	38	56	23.5	upon request
	7385363	BY16-240	10	16	38	56	23.5	



Nominal section (mm²)



Packing




Stud size



Type of dies


Unless otherwise stated, all dimensions are in millimeters.

Non-insulated Copper Brazed Wire Pins



General features

- ✓ Material: tin-plated copper.
- ✓ Brazed barrel.



mm ²	Item code	x3	Part No.	W	F	L	E	Ø i	Ø e	
6 - 10	7380450		BY10W13D	4.3	14	22	8	4.5	6.9	..DMB10
10 - 16	7380451		BY16W17D	5.5	16	26	10	5.8	8.4	..DMB16
16 - 25	7380452		BY25W17D	6.8	20	33.5	13.5	7	9.5	..DMB25
25 - 35	7380453		BY35W23D	8	24.5	40.5	16	8.4	11.8	..DMB35
35 - 50	7380454		BY50W23D	9.5	26	45	19	9.6	13.6	..DMB50
50 - 70	7380455		BY70W26D	11	31	55	24	11.4	15.8	..DMB70
70 - 95	7380427		BY95W26D	12.5	31	55	24	13.5	18.9	..DMB95



Nominal section (mm²)



Packing



Stud size



Type of dies

Unless otherwise stated, all dimensions are in millimeters.