


Copper Butt Connector



General features

- ✓ Electrolytic copper (EN 13600).
- ✓ Electrolytic tin-plating process.
- ✓ Funnel entry.
- ✓ Other treatments upon request.



Ø i

Ø e

L



| mm ² | Item code | Part No. | | Ø i | Ø e | L | |
|-----------------|-----------|----------|-----|------|------|-----|--------|
| 6 | 7435061 | DEM6 | 100 | 3.5 | 6.5 | 24 | ..R6 |
| 10 | 7435071 | DEM10 | 100 | 4.5 | 7 | 28 | ..R10 |
| 16 | 7435081 | DEM16 | 100 | 5.5 | 8.5 | 34 | ..R16 |
| 25 | 7435091 | DEM25 | 100 | 7 | 10 | 38 | ..R25 |
| 35 | 7435101 | DEM35 | 100 | 8.5 | 12 | 42 | ..R35 |
| 50 | 7435111 | DEM50 | 50 | 10 | 14 | 48 | ..R50 |
| 70 | 7435121 | DEM70 | 50 | 12 | 16.5 | 52 | ..R70 |
| 95 | 7435131 | DEM95 | 50 | 13.5 | 18 | 59 | ..R95 |
| 120 | 7435141 | DEM120 | 50 | 15 | 19.5 | 62 | ..R120 |
| 150 | 7435151 | DEM150 | 50 | 16.5 | 21 | 72 | ..R150 |
| 185 | 7435161 | DEM185 | 50 | 19 | 24 | 72 | ..R185 |
| 240 | 7435171 | DEM240 | 50 | 21 | 26 | 82 | ..R240 |
| 300 | 7435181 | DEM300 | 25 | 23.5 | 29.5 | 102 | ..R300 |
| 400 | 7435191 | DEM400 | 25 | 27 | 34 | 102 | ..R400 |



Conductor size (mm²)



Packing



Type of dies

Unless otherwise stated, all dimensions are in millimeters.