




Preinsulated Copper Tubular Lugs for Flexible Cables



General features

- ✓ Material: tin-plated copper.
- ✓ Insulation sleeve: nylon.



PR-CU Series



Item code

Part No.



W L Ø i C1 C2



mm ²	Item code	Part No.	Packing	Ø mm	Ø mm	W	L	Ø i	C1	C2
10	7391010	PR10-4CU	100	8	4	11	34.5	4.6	5.3	3.8
	7391020	PR10-5CU	100		5	11	36.5		6.3	4.8
	7391030	PR10-6CU	100		6	11	38.5		7.3	5.8
	7391040	PR10-8CU	100		8	15	42.5		9.3	7.8
	7391050	PR10-10CU	100		10	15	46.5		11.3	9.8
16	7391100	PR16-4CU	100	9.4	4	12	38	5.8	5.3	3.8
	7391110	PR16-5CU	100		5	12	40		6.3	4.8
	7391120	PR16-6CU	100		6	12	42		7.3	5.8
	7391130	PR16-8CU	100		8	16	46		9.3	7.8
	7391140	PR16-10CU	100		10	16	50		11.3	9.8
25	7391150	PR16-12CU	100	11.5	12	17	53.5	7	14.3	8.9
	7391160	PR25-4CU	100		4	14	41.5		5.3	3.8
	7391170	PR25-5CU	100		5	14	43.5		6.3	4.8
	7391180	PR25-6CU	100		6	14	45.5		7.3	5.8
	7391190	PR25-8CU	100		8	18	49.5		9.3	7.8
	7391200	PR25-10CU	100		10	18	53.5		11.3	9.8
	7391210	PR25-12CU	100		12	18	57.5		13.8	11.3
35	7391220	PR25-14CU	100	14	14	23	68.5	8.9	19.3	16.8
	7391230	PR35-5CU	50		5	17	48.5		6.3	4.8
	7391240	PR35-6CU	50		6	17	50.5		7.3	5.8
	7391250	PR35-8CU	50		8	17	54.5		9.3	7.8
	7391260	PR35-10CU	50		10	19	58.5		11.3	9.8
	7391270	PR35-12CU	50		12	19	62.5		13.8	11.3
50	7391280	PR35-14CU	50	15.5	14	23	66.5	10	15.3	13.8
	7391290	PR50-6CU	50		6	19	57		7.3	5.8
	7391300	PR50-8CU	50		8	19	61		9.3	7.8
	7391310	PR50-10CU	50		10	19	65		11.3	9.8
	7391320	PR50-12CU	50		12	22	69		13.8	11.3
	7391330	PR50-14CU	50		14	22	73		15.3	13.8
70	7391340	PR50-16CU	50	18	16	25	76	11.3	17.3	14.8
	7391350	PR70-6CU	25		6	22	67		9.3	7.8
	7391360	PR70-8CU	25		8	22	67		9.3	7.8
	7391370	PR70-10CU	25		10	22	71		11.3	9.8
	7391380	PR70-12CU	25		12	22	75		13.8	11.3
	7391390	PR70-14CU	25		14	26	79		15.3	13.8
95	7391400	PR70-16CU	25	20	16	26	82	13.5	17.3	14.8
	7391410	PR95-6CU	25		6	26	71.5		9.3	7.8
	7391420	PR95-8CU	25		8	26	71.5		9.3	7.8
	7391430	PR95-10CU	25		10	26	75.5		11.3	9.8
	7391440	PR95-12CU	25		12	26	79.5		13.8	11.3
	7391450	PR95-14CU	25		14	26	83.5		15.3	13.8
	7391460	PR95-16CU	25		16	30	86.5		17.3	14.8
120	7391470	PR95-18CU	25	23	18	30	95.5	17	21.3	19.8
	7391480	PR95-20CU	25		20	30	95.5		21.3	19.8
	7390525	PR120-8F	20		8	31	95		14	14
	7390526	PR120-10F	20		10	31	95		14	14
	7390527	PR120-12F	20		12	31	98		16	14
7390528	PR120-14F	20	14	31	98	16	15			
7390529	PR120-16F	20	16	31	98	16	15			

MY70ME

MY286



Conductor size (mm²)



Packing



Cable insulation max Ø



Stud size



Type of dies

Unless otherwise stated, all dimensions are in millimeters.