


SCHUKO socket outlets

- for 4-hole screw fitting

SCHUKO socket outlets with plug-in terminals

- thermoplastic centre plates and bases
- contacts made of copper alloy

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with hinged cover and imprint "IP44" and contact protection box.



SCHUKO socket outlet

- plug-in terminals



Rated voltage 250 V~

Rated current 16 A

Earth bracket clamping forces according to TNO requirements.

Standard NEN 1010

Connection terminals according to IEC 60884-1

| Design | Order no. | PU |
|------------------|---------------------|-----|
| brown matt | 8 4778 25 01 | 200 |
| anthracite matt | 8 4778 25 05 | 200 |
| grey matt | 8 4778 25 06 | 200 |
| polar white matt | 8 4778 25 02 | 200 |
| brown matt | 9 4778 25 01 | 10 |
| anthracite matt | 9 4778 25 05 | 10 |
| grey matt | 9 4778 25 06 | 10 |
| polar white matt | 9 4778 25 02 | 10 |
| black matt | 9 4778 25 03 | 10 |



SCHUKO socket outlet

- enhanced contact protection
- plug-in terminals



Rated voltage 250 V~

Rated current 16 A

Earth bracket clamping forces according to TNO requirements.

Standard NEN 1010

Connection terminals according to IEC 60884-1


Enhanced contact protection (child protection) according to IEC 60884-1

| Design | Order no. | PU |
|------------------|---------------------|-----|
| brown matt | 8 4779 25 01 | 200 |
| anthracite matt | 8 4779 25 05 | 200 |
| grey matt | 8 4779 25 06 | 200 |
| polar white matt | 8 4779 25 02 | 200 |
| brown matt | 9 4779 25 01 | 10 |
| anthracite matt | 9 4779 25 05 | 10 |
| grey matt | 9 4779 25 06 | 10 |
| polar white matt | 9 4779 25 02 | 10 |
| black matt | 9 4779 25 03 | 10 |



SCHUKO socket outlets with screw terminals

- thermoplastic centre plates
- duroplast base
- contacts made of copper alloy

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853), frame with hinged cover and imprint "IP44" and contact protection box.

 **SCHUKO socket outlet** ▶ 210



- screw terminals



Rated voltage 250 V~
Rated current 16 A

Connection terminals according to IEC 60884-1

| Suitable for | Order no. | Page |
|--|-----------|------|
| Contact protection box Ø 45 mm | 9 1820 .. | 63 |
| Contact protection box Ø 49 mm | 9 188 .. | 63 |
| Contact protection box 2gang | 9 191 .. | 63 |
| Contact protection box 3gang | 9 1933 | 64 |
| Optional | | |
| Sealing for IP44 applications | 9 1853 | 78 |
| Frame with hinged cover and imprint "IP44" | 8 1828 .. | 77 |

| Design | Order no. | PU |
|------------------|---------------------|-----|
| brown matt | 8 4185 25 01 | 200 |
| anthracite matt | 8 4185 25 05 | 200 |
| grey matt | 8 4185 25 06 | 200 |
| polar white matt | 8 4185 25 02 | 200 |
| black matt | 8 4185 05 | 200 |
| | | |
| brown matt | 9 4185 25 01 | 10 |
| anthracite matt | 9 4185 25 05 | 10 |
| grey matt | 9 4185 25 06 | 10 |
| polar white matt | 9 4185 25 02 | 10 |
| black matt | 9 4185 05 | 10 |



 **SCHUKO socket outlet** ▶ 210



- enhanced contact protection
- screw terminals






Rated voltage 250 V~
Rated current 16 A

Connection terminals according to IEC 60884-1
Enhanced contact protection (child protection) according to IEC 60884-1

| Suitable for | Order no. | Page |
|--|-----------|------|
| Contact protection box Ø 45 mm | 9 1820 .. | 63 |
| Contact protection box Ø 49 mm | 9 188 .. | 63 |
| Contact protection box 2gang | 9 191 .. | 63 |
| Contact protection box 3gang | 9 1933 | 64 |
| Optional | | |
| Sealing for IP44 applications | 9 1853 | 78 |
| Frame with hinged cover and imprint "IP44" | 8 1828 .. | 77 |

| Design | Order no. | PU |
|------------------|---------------------|-----|
| brown matt | 8 4195 25 01 | 200 |
| anthracite matt | 8 4195 25 05 | 200 |
| grey matt | 8 4195 25 06 | 200 |
| polar white matt | 8 4195 25 02 | 200 |
| black matt | 8 4195 05 | 200 |
| | | |
| brown matt | 9 4195 25 01 | 10 |
| anthracite matt | 9 4195 25 05 | 10 |
| grey matt | 9 4195 25 06 | 10 |
| polar white matt | 9 4195 25 02 | 10 |
| black matt | 9 4195 05 | 10 |






| | | | |
|---|---|---------------------|-----------------------------|
|  | SCHUKO socket outlet 45° | | ▶ 210 |
| | - screw terminals | | - for diagonal installation |
| |  | | |
| | Rated voltage | 250 V~ | |
| | Rated current | 16 A | |
| | Connection terminals according to IEC 60884-1 | | |
| | Design | Order no. | PU |
| | brown matt | 8 4185 25 21 | 200 |
| | anthracite matt | 8 4185 25 25 | 200 |
| | grey matt | 8 4185 25 26 | 200 |
| polar white matt | 8 4185 25 22 | 200 | |
| black matt | 8 4185 25 | 200 | |
|  | black matt | 9 4185 25 | 10 |

SCHUKO socket outlets with insulation-piercing terminals

- New: Insulation-piercing terminals (IPT) for quick and easy connection with the joining tool, order no. 8 1726 25 81
- VDE approval
- Up to 2 flexible conductors with a cross section of 2.5 mm² can be connected for each IPT contact; wires do not have to be stripped in advance.
- Enables multiple socket outlets to be looped through without breaking the conductors.
- IPT contacts made from copper alloy, tin-plated
- thermoplastic centre plates and bases
- Base with snap-on safety cap

 Marked items are only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with sealing (order no. 9 1853 01) and frame with hinged cover and imprint "IP44".

| | | | |
|---|---|---------------------|-------|
|  | SCHUKO socket outlet | | ▶ 212 |
| | - insulation-piercing terminals | | |
| |  | | |
| | Rated voltage | 250 V~ | |
| | Rated current | 16 A | |
| | Conductor cross-section (flexible) | 2.5 mm ² | |
| | Earth bracket clamping forces according to TNO requirements. | | |
| | Not suitable for contact protection boxes (cavity walls). | | |
| | Connection terminals according to IEC 60884-1 | | |
| | Design | Order no. | PU |
| anthracite matt | ★ 8 4800 25 05 | 200 | |
| grey matt | ★ 8 4800 25 06 | 200 | |
| polar white matt | ★ 8 4800 25 02 | 200 | |
| black matt | ★ 8 4800 25 08 | 200 | |
| red matt | ★ 8 4800 25 07 | 200 | |
| green matt | ★ 8 4800 25 03 | 200 | |
| orange matt | ★ 8 4800 25 04 | 200 | |
|  | | | |



SCHUKO socket outlet

▶ 212

- enhanced contact protection
- insulation-piercing terminals



| | |
|------------------------------------|---------------------|
| Rated voltage | 250 V~ |
| Rated current | 16 A |
| Conductor cross-section (flexible) | 2.5 mm ² |

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

| Suitable for Optional | Order no. | Page |
|---|-----------|------|
| Sealing IP44 for socket outlets with insulation displacement contacts | 9 1853 01 | 79 |
| Frame with hinged cover and imprint "IP44" | 8 1828 .. | 77 |

| Design | Order no. | PU |
|------------------|----------------|-----|
| anthracite matt | ★ 8 4801 25 05 | 200 |
| grey matt | ★ 8 4801 25 06 | 200 |
| polar white matt | ★ 8 4801 25 02 | 200 |
| black matt | ★ 8 4801 25 08 | 200 |
| red matt | ★ 8 4801 25 07 | 200 |
| green matt | ★ 8 4801 25 03 | 200 |
| orange matt | ★ 8 4801 25 04 | 200 |



SCHUKO socket outlet with control LED

▶ 212

- insulation-piercing terminals

- with green control LED as function light



| | |
|------------------------------------|---------------------|
| Rated voltage | 250 V~ |
| Rated current | 16 A |
| LED current | 1 mA |
| Conductor cross-section (flexible) | 2.5 mm ² |

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

| Suitable for Optional | Order no. | Page |
|---|-----------|--------------|
| Frame with hinged cover and imprint "IP44" | | upon request |
| Sealing IP44 for socket outlets with insulation displacement contacts | 9 1853 01 | 79 |

| Design | Order no. | PU |
|------------------|----------------|-----|
| anthracite matt | ★ 8 4800 25 15 | 200 |
| grey matt | ★ 8 4800 25 16 | 200 |
| polar white matt | ★ 8 4800 25 12 | 200 |
| black matt | ★ 8 4800 25 18 | 200 |
| red matt | ★ 8 4800 25 17 | 200 |
| green matt | ★ 8 4800 25 13 | 200 |
| orange matt | ★ 8 4800 25 14 | 200 |



New  **SCHUKO socket outlet with control LED** ▶ 212



- enhanced contact protection
- insulation-piercing terminals



| | |
|------------------------------------|---------------------|
| Rated voltage | 250 V~ |
| Rated current | 16 A |
| LED current | 1 mA |
| Conductor cross-section (flexible) | 2.5 mm ² |

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- with green control LED as function light

| Suitable for | Order no. | Page |
|---|-----------|--------------|
| Optional | | |
| Frame with hinged cover and imprint "IP44" | | upon request |
| Sealing IP44 for socket outlets with insulation displacement contacts | 9 1853 01 | 79 |

| Design | Order no. | PU |
|------------------|----------------|-----|
| anthracite matt | ★ 8 4801 25 15 | 200 |
| grey matt | ★ 8 4801 25 16 | 200 |
| polar white matt | ★ 8 4801 25 12 | 200 |
| black matt | ★ 8 4801 25 18 | 200 |
| red matt | ★ 8 4801 25 17 | 200 |
| green matt | ★ 8 4801 25 13 | 200 |
| orange matt | ★ 8 4801 25 14 | 200 |



New  **SCHUKO socket outlet 45°** ▶ 212



- insulation-piercing terminals



| | |
|------------------------------------|---------------------|
| Rated voltage | 250 V~ |
| Rated current | 16 A |
| Conductor cross-section (flexible) | 2.5 mm ² |

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

- for diagonal installation

| Suitable for | Order no. | Page |
|---|-----------|------|
| Optional | | |
| Sealing IP44 for socket outlets with insulation displacement contacts | 9 1853 01 | 79 |
| Frame with hinged cover and imprint "IP44" | 8 1828 .. | 77 |

| Design | Order no. | PU |
|------------------|----------------|-----|
| anthracite matt | ★ 8 4850 25 05 | 200 |
| grey matt | ★ 8 4850 25 06 | 200 |
| polar white matt | ★ 8 4850 25 02 | 200 |
| black matt | ★ 8 4850 25 08 | 200 |
| red matt | ★ 8 4850 25 07 | 200 |
| green matt | ★ 8 4850 25 03 | 200 |
| orange matt | ★ 8 4850 25 04 | 200 |





SCHUKO socket outlet 45°

▶ 212

- enhanced contact protection
- insulation-piercing terminals



| | |
|------------------------------------|---------------------|
| Rated voltage | 250 V~ |
| Rated current | 16 A |
| Conductor cross-section (flexible) | 2.5 mm ² |

- for diagonal installation

| Suitable for | Order no. | Page |
|---|-----------|------|
| Optional | | |
| Sealing IP44 for socket outlets with insulation displacement contacts | 9 1853 01 | 79 |
| Frame with hinged cover and imprint "IP44" | 8 1828 .. | 77 |

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

| Design | Order no. | PU |
|------------------|----------------|-----|
| anthracite matt | ★ 8 4851 25 05 | 200 |
| grey matt | ★ 8 4851 25 06 | 200 |
| polar white matt | ★ 8 4851 25 02 | 200 |
| black matt | ★ 8 4851 25 08 | 200 |
| red matt | ★ 8 4851 25 07 | 200 |
| green matt | ★ 8 4851 25 03 | 200 |
| orange matt | ★ 8 4851 25 04 | 200 |



SCHUKO socket outlet 45° with control LED

▶ 212

- insulation-piercing terminals



| | |
|------------------------------------|---------------------|
| Rated voltage | 250 V~ |
| Rated current | 16 A |
| LED current | 1 mA |
| Conductor cross-section (flexible) | 2.5 mm ² |

- with green control LED as function light
- for diagonal installation

| Suitable for | Order no. | Page |
|---|-----------|--------------|
| Optional | | |
| Frame with hinged cover and imprint "IP44" | | upon request |
| Sealing IP44 for socket outlets with insulation displacement contacts | 9 1853 01 | 79 |

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

| Design | Order no. | PU |
|------------------|----------------|-----|
| anthracite matt | ★ 8 4850 25 15 | 200 |
| grey matt | ★ 8 4850 25 16 | 200 |
| polar white matt | ★ 8 4850 25 12 | 200 |
| black matt | ★ 8 4850 25 18 | 200 |
| red matt | ★ 8 4850 25 17 | 200 |
| green matt | ★ 8 4850 25 13 | 200 |
| orange matt | ★ 8 4850 25 14 | 200 |



Berker Integro - Module inserts

SCHUKO socket outlets

New  **SCHUKO socket outlet 45° with control LED** ▶ 212



- enhanced contact protection
- insulation-piercing terminals



| | |
|------------------------------------|---------------------|
| Rated voltage | 250 V~ |
| Rated current | 16 A |
| LED current | 1 mA |
| Conductor cross-section (flexible) | 2.5 mm ² |

Earth bracket clamping forces according to TNO requirements.

Not suitable for contact protection boxes (cavity walls).

Connection terminals according to IEC 60884-1

Enhanced contact protection (child protection) according to IEC 60884-1

- with green control LED as function light
- for diagonal installation

| Suitable for | Order no. | Page |
|---|-----------|--------------|
| Optional | | |
| Frame with hinged cover and imprint "IP44" | | upon request |
| Sealing IP44 for socket outlets with insulation displacement contacts | 9 1853 01 | 79 |

| Design | Order no. | PU |
|------------------|----------------|-----|
| anthracite matt | ★ 8 4851 25 15 | 200 |
| grey matt | ★ 8 4851 25 16 | 200 |
| polar white matt | ★ 8 4851 25 12 | 200 |
| black matt | ★ 8 4851 25 18 | 200 |
| red matt | ★ 8 4851 25 17 | 200 |
| green matt | ★ 8 4851 25 13 | 200 |
| orange matt | ★ 8 4851 25 14 | 200 |



New **Joining tool for Berker Integro socket outlets with IPT technology** ▶ 212



| Design | Order no. | PU |
|-----------|----------------|-----|
| blue matt | ★ 8 1726 25 81 | 200 |
| blue matt | ★ 9 1726 25 81 | 10 |

