

Berker Integro Design Pure

The purist for built-in installations. Consistently clear, angular and with an absolutely planar surface – modern and compact. And consequently the ideal component for aesthetic ambience. The granite-black, silk-matt lacquered design guarantees a special operating experience. An innovative refined surface lacquer offers exceptional haptics for the connoisseur.





04

Page

Frames	100
Surface-mounted housing	100








Product examples

Berker Integro

Design Pure



Dimensions

Frame 1-3gang (W x H)
 1-gang: 59.5 x 59.5 mm
 2-gang: 59.5 x 119 mm
 3-gang: 59.5 x 178.5 mm





Frames/Covers/ Central inserts

Plastic, glossy

polar white similar to RAL 9010
black similar to RAL 9005

Plastic, galvanised


chrome glossy similar to RAL 9023
chrome matt similar to RAL 9006



Plastic, lacquered

granite black, silk matt similar to RAL 7026
stainless steel similar to RAL 9022

Frames



Frame 1gang

▶ 214

Design	Order no.	PU
polar white glossy	9 1975 25 09	10
black glossy	9 1975 25 10	10
granite black, silk matt, lacquered	9 1975 25 45	10
chrome matt, galvanised	9 1975 25 28	10
chrome glossy, galvanised	9 1975 25 18	10
stainless steel matt, lacquered	9 1975 25 24	10



Frame 2gang

– for vertical and horizontal mounting

▶ 214

Design	Order no.	PU
polar white glossy	9 1976 25 09	2
black glossy	9 1976 25 10	2
granite black, silk matt, lacquered	9 1976 25 45	2
chrome matt, galvanised	9 1976 25 28	2
chrome glossy, galvanised	9 1976 25 18	2
stainless steel matt, lacquered	9 1976 25 24	2



Frame 3gang

– for vertical and horizontal mounting

▶ 214

Design	Order no.	PU
polar white glossy	9 1978 25 09	2
black glossy	9 1978 25 10	2
granite black, silk matt, lacquered	9 1978 25 45	2
chrome matt, galvanised	9 1978 25 28	2
chrome glossy, galvanised	9 1978 25 18	2
stainless steel matt, lacquered	9 1978 25 24	2

Frames with hinged cover



Frame with hinged cover

– for covering of socket outlets

▶ 214

Design	Order no.	PU
polar white glossy	9 1828 25 09	10
black glossy	9 1828 25 10	10
granite black, silk matt, lacquered	9 1828 25 45	10
chrome matt, galvanised	9 1828 25 28	10
chrome glossy, galvanised	9 1828 25 18	10
Stainless steel matt, lacquered	9 1828 25 24	10

Surface-mounted housing



Surface-mounted housing high

▶ 214

Dimensions (W x H x D) 59.5 x 59.5 x 41 mm

- with cable entry
- for mounting on combustible base surface
- to built-on installation of devices

Suitable for	Order no.	Page
Wire and duct entry	1813 ..	66

Design	Order no.	PU
--------	-----------	----

without strain relief

polar white glossy	9 1151 25 09	10
black glossy	9 1151 25 10	10

with strain relief

polar white glossy	9 1151 25 19	10
black glossy	9 1151 25 20	10





Surface-mounted housing flat

▶ 214

Dimensions (W x H x D) 59.5 x 59.5 x 16 mm
 - for mounting on combustible base surface
 - to built-on installation of switches and push-buttons

Design Order no. PU

without strain relief

polar white glossy **9 1152 25 29** 10

with 1 strain relief

polar white glossy **9 1152 25 59** 10



with 2 strain reliefs

polar white glossy **9 1152 25 69** 10



Surface-mounted spacer ring

▶ 214

Dimensions (W x H x D) 59.5 x 59.5 x 10 mm
 - for the reduction of the installation depth of the devices and surf.-mount. of switches and push-b.

Design Order no. PU

polar white glossy **9 1825 25 12** 10

black glossy **9 1825 25 10** 10

chrome matt, lacquered **9 1825 25 68** 10

Stainless steel matt, lacquered **9 1825 25 24** 10

