



Audible and Visual Warning Device Selection

deegree
beaconlamps.com

	VISUAL										SOUNDER / COMBI-SOUNDER			
Series														
	PSC LED Beacon	XFD Xenon Beacon	PSD LED Beacon	XFB Xenon Strobe	PSB LED Beacon	RFH Rotating Mirror Beacon	PSH LED Beacon	Modular Stacklights	IPN Traffic Lights	MIH Traffic Lights	IAS-C Sounder	ISB-C Sounder Beacon	IAS-E Sounder	ISB-E Sounder Beacon
Select Required Voltage														
Voltage	24-230Vuc	12V-24Vdc 115Vac 230Vac	12Vdc 24-230Vuc	12V-24Vdc 115Vac 230Vac	12-48Vdc 48-230Vuc	12-48Vdc 115-230Vuc	12Vdc 24Vdc 115-230Vuc	12Vdc 24-230Vuc BASE	24Vuc 115Vac 230Vac	24-36Vdc 115-230Vuc	12-24Vdc 55-230Vuc	12-36Vdc 55-230Vuc	12Vdc 24-48Vdc 48-55Vuc 115-230Vuc	12Vdc 24Vdc 48-55Vuc 115-230Vuc
Select Sound Output														
Sound								94dB (4 tones)			112dB (64 tones)	112dB (32 tones)	114dB (64 tones)	114dB (64 tones)
Select Required Light Source														
Light source	24 LEDs Flashing Static 130° light axis	2.5 Joule Xenon Strobe 360° light axis	30 LEDs 7 Flashing Modes Static 360° light axis	5 Joule Xenon Strobe 360° light axis	36 LEDs 7 Flashing Modes Static 360° light axis	48 LEDs 360° light axis	120 LEDs 7 Flashing Modes Static 360° light axis	30 LEDs 7 Flashing Modes Static 360° light axis	2-way 55 LEDs per colour 3-way 60 LEDs per colour	48 LEDs per colour		15 LEDs Pulses in time with sound Flashing-Only (no sound option)		15 LEDs Pulsed Light & Sound may be selected independently 30° light axis
Select Signal Colour - RED - Danger or Emergency/Fault. AMBER - Warning or Be aware. GREEN - Safe or Normal operation. BLUE - Mandatory significance or A change is underway. CLEAR - No specific meaning. YELLOW - Similar to Amber. PURPLE - Danger (distinct alternative to RED)														
Colour	R A G B C Y	R A G B C Y P	R A G B C Y	R A G B C Y	R A G B C Y	R A G B C Y	R A G B C	R A G B C Y P	R G R A G	R G R A G		R A G B C		R A G B C
Additional Information														
IP Rating	IP69K Dust-tight High pressure water	IP65 Dust-tight Low pressure water	IP65 Dust-tight Low pressure water	IP66 Dust-tight Higher pressure water	IP66 Dust-tight Higher pressure water	IP65 Dust-tight Low pressure water	IP65 Dust-tight Low pressure water	IP65 (Not ASA) Dust-tight Low pressure water	IP65 Dust-tight Low pressure water	IP65 Dust-tight Low pressure water	IP66 Dust-tight Higher pressure water	IP66 Dust-tight Higher pressure water	IP65 Dust-tight Low pressure water	IP65 Dust-tight Low pressure water
Operating Temp	-40°C to +55°C	-20°C to +55°C	-20°C to +55°C	-40°C to +55°C	-40°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C
Dimensions	85 x 94 dia.	102 x 79 dia.	102 x 79 dia.	135 x 94 dia.	135 x 94 dia.	225 x 175 dia.	225 x 175 dia.	Stack 79 dia.	200 x 150 x 80	300 x 150 x 151 450 x 150 x 151	85 x 94 dia.	85 x 94 dia.	117 x 146 dia.	117 x 146 dia.
Order Code Example	PSC/UC/24-230/ LED/R	XFD/AC/230/SH/2. 5J/G	PSD/UC/24-230/ LED/A	XFB/DC/12-24/ SH/5J/R	PSB/DC/12-48/HP- LED/B	RFH/DC/12-48/RM- LED/R	PSH/DC/24/LED/A	BCSA PSA/UC/24-23-/ LED/R PSA/UC/24-23-/ LED/G ASA/UC/12-230	IPN/AC/115/ LED/002/RG IPN/AC/230/ LED/018/RAG	MIH/2U/DC/24-36/ LED/RG	IAS-C/UC/55-230/ WHITE	ISB-C/DC/12-36/RED	IAS-E/DC/24-48/RED	ISB-E/UC/115-230/ LED/A

Ask about our range of Accessories (Cage guards, Wall brackets and Mounting options) to facilitate your install



D G Controls Limited
Cadley Hill Road
Swadlincote
Derbyshire, UK
DE11 9TB

Tel: +44 1283 550850
Fax: +44 1283 550776
e-mail: mail@beaconlamps.com
www: https://beaconlamps.com

