



**18 Time relays**



- Modular versions for modular-slot switchboards, mounting on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing via pull out tabs
- Plug-in or flush-mount version
- Version programmable with NFC and APP
- Wide range of functions and time scales
- High accuracy and repeatability of the time settings.

	<b>SEC. - PAGE</b>
<b>Modular versions</b>	
On delay. Multiscale. Multivoltage .....	18 - 2
Multifunction. Multiscale. Multivoltage. 1 relay output .....	18 - 2
Multifunction. Multiscale. Multivoltage. 1 relay output, with NFC and APP .....	18 - 2
Multifunction. Multiscale. Multivoltage. 2 relay outputs .....	18 - 3
Recycle, independent timings. Multiscale. Multivoltage .....	18 - 3
Off delay. Multiscale. Multivoltage .....	18 - 3
For starting. Multiscale. Multivoltage .....	18 - 4
For staircase with “zero crossing” load switching .....	18 - 4
<b>Plug-in and flush-mount version, 48x48mm/1.9x1.9”</b>	
On delay. Multiscale. Multivoltage .....	18 - 5
On delay. Multiscale. Single voltage .....	18 - 5
Multifunction. Multivoltage. Multiscale .....	18 - 5
Accessories .....	18 - 5
<b>Dimensions .....</b>	<b>18 - 6</b>
<b>Wiring diagrams .....</b>	<b>18 - 6</b>
<b>Technical characteristics .....</b>	<b>18 - 10</b>



Page 18-2

**MODULAR TIME RELAYS**

- Suitable for modular-slot switchboards
- Selectable time ranges and functions with potentiometers on front or via NFC and APP
- LED indication
- Mounting on 35mm DIN rail or screw fixing
- Screw terminals.



Page 18-5

**PLUG-IN AND FLUSH-MOUNT TIME RELAYS, 48X48MM**

- Flush and internal panel mounting
- Time ranges: 0.05s...10h
- LED indication
- 8 and 11-pin sockets for panel mounting.



# 18 Time relays

## Modular version

### On delay time relay. Multiscale. Multivoltage



TMP

Order code	Time of scale range	Rated auxiliary supply voltage	Qty per pkg	Wt
		[V]	n°	[kg]
<b>TMP</b>	0.1...1s 1...10s 6...60s 1...10min 6min...1h 1...10h 0.1...1 day 1...10 days ON only OFF only	24...48VDC 24...240VAC	1	0.078
<b>TMPA440</b>	0.1...1s 1...10s 6...60s 1...10min	380...440VAC	1	0.078

#### General characteristics

- Electronic time relay, multiscale, multivoltage. On delay, delay on make, with 1 relay output with 1 changeover contact (SPDT) start at relay energising for TMP
- Electronic time relay, multiscale with 2 normally open (N/O-SPST) contacts with common pole for TMPA440.
- Delay time adjustable on front by rotary switch: 10...100%
- Green LED indicator for power on
- Red LED indicator for relay state; flashing for delay and steady when relay energised
- Modular DIN 43880 housing, 1 module suitable for fixing on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing
- IEC degree of protection: IP40 on front (only when mounted in housing or electric board with IP40); IP20 on terminals.

#### Certifications and compliance

Certifications obtained: EAC; UL Listed, for USA and Canada (cULus - File E93601), CCC.  
Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n° 14.

### Multifunction time relay. Multiscale. Multivoltage. 1 relay output



TMM1

Order code	Time of scale range	Rated auxiliary supply voltage	Qty per pkg	Wt
		[V]	n°	[kg]
<b>TMM1</b>	0.1...1s 1...10s 6...60s 1...10min 6min...1h 1...10h 0.1...1 day 1...10 days ON only OFF only	12...240V AC/DC	1	0.086

#### General characteristics

- Electronic time relay, multifunction, multiscale, multivoltage, with 1 relay output with 1 changeover contact (SPDT)
- Enabling input
- Selectable functions: (a) On delay. (b) Pulse on relay energising with start when energised. (c) Symmetrical flasher starting with OFF. (d) Symmetrical flasher starting with ON. (e) Off delay; relay energising at external contact closing with start on break. (f) Pulse on relay energising with start on external contact closing. (g) Pulse on relay energising with start on external contact opening. (h) On-off delay. Delay on make, with start at external contact closing, and delay at break, with start at external contact opening. (i) Internal ON/OFF trigger with relay contact closing or operating at each closing of an external contact. (j) Pulse generator.
- Delay time adjustable on front by rotary switch: 10...100%
- Green LED indicator for power on
- Red LED indicator for relay state; flashing for delay and steady when relay energised
- Modular DIN 43880 housing, 1 module suitable for fixing on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing
- IEC degree of protection: IP40 on front (only when mounted in housing or electric board with IP40); IP20 on terminals.

#### Certifications and compliance

Certifications obtained: UL Listed, for USA and Canada (cULus - File E93601); EAC.  
Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n° 14.

### Multifunction time relay. Multiscale. Multivoltage. 1 relay output. Programmable with NFC and APP



TMM1NFC





The app can be downloaded from Google Play Store and App Store.



Order code	Time of scale range	Rated auxiliary supply voltage	Qty per pkg	Wt
		[V]	n°	[kg]
<b>TMM1NFC</b>	0.1s... 999days ON only OFF only	12...240V AC/DC	1	0.086

Simple and intuitive programming with LOVATO **NFC** App thanks to the graphic interface that displays the selected function and parameters directly on the screen of the smartphone, eliminating the need to consult the manual.



#### General characteristics

- Electronic time relay, multifunction, multiscale, multivoltage, with 1 relay output with changeover contact (SPDT), with NFC technology and LOVATO **NFC** App
- Command input for the enabling of the function or to pause the timing
- 40 selectable functions. For details consult the technical manual on the website [www.LovatoElectric.com](http://www.LovatoElectric.com)
- NFC connectivity for the programming of the parameters with the LOVATO **NFC** App freely downloadable from Google Play Store and App Store
- Simple, fast and intuitive programming
- Very high accuracy and repeatability of the settings
- Internal counter which stops the function when the relay output reaches a programmable number of closures
- Possibility to save the program on smartphone or tablet to be copied on others TMM1NFC, even with device powered off
- Possibility to protect the settings with a password
- QR code for the direct connection to the LOVATO Electric website for the download of the technical manual
- Green LED indicator for power on
- Red LED indicator for relay state; flashing for delay and steady when relay energised
- Modular DIN 43880 housing (1 module), suitable for fixing on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing
- IEC degree of protection: IP40 on front (only when mounted in housing or electric board with IP40), IP20 on terminals.

#### Certifications and compliance

Certifications: cULus, EAC, CCC.  
Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n°14.

# 18 Time relays

## Modular version

### Multifunction time relay. Multiscale. Multivoltage. 2 relay outputs



TMM2

Order code	Time of scale range	Rated auxiliary supply voltage [V]	Qty per pkg n°	Wt [kg]
<b>TMM2</b>	0.1...1s 1...10s 6...60s 1...10min 6min...1h 1...10h 0.1...1 day 1...10 days ON only OFF only	12...240V AC/DC	1	0.094

#### General characteristics

- Electronic time relay, multifunction, multiscale, multivoltage
- 2 relay outputs, one with 1 delayed changeover (C/O-SPDT) contact and the other with 1 normally open (N/O-SPST) contact, programmable as instantaneous or delayed
- Enabling input
- Selectable functions: (a) On delay; delay on make with start at relay energising. (b) Pulse on relay energising with start when energised. (c) Flasher starting with OFF interval. Equal timing recycle. (d) Flasher starting with ON interval. Equal timing recycle. (e) Off delay; relay energising at external contact closing with start on break. (f) Pulse on relay energising with start on external contact closing. (g) Pulse on relay energising with start on external contact opening. (h) On-off delay. Delay on make, with start at external contact closing, and delay at break, with start at external contact opening. (i) Internal ON/OFF trigger with relay contact closing or operating at each closing of an external contact. (j) Pulse generator, unequal timing recycle; starting with OFF pulse time and 0.5s ON pulse.
- Delay time adjustable on front by rotary switch: 10...100%
- Green LED indicator for power on
- Red LED indicator for relay state; flashing for delay and steady when relay energised
- Modular DIN 43880 housing, 1 module suitable for fixing on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing
- IEC degree of protection: IP40 on front (only when mounted in housing or electric board with IP40); IP20 on terminals.

#### Certifications and compliance

Certifications obtained: UL Listed, for USA and Canada (cULus - File E93601) as Auxiliary Devices - Timers; EAC. Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n° 14.

### Recycle time relay, independent timings. Multiscale. Multivoltage



TMPL

Order code	Time of scale range	Rated auxiliary supply voltage [V]	Qty per pkg n°	Wt [kg]
<b>TMPL</b>	0.1...1s 1...10s 6...60s 1...10min 6min...1h 1h...10h 0.1...1 day 1...10 days 3...30 days 10...100 days	12...240V AC/DC	1	0.082

#### General characteristics

- Recycle time relay with asymmetrical timings, multiscale, multivoltage
- 1 relay output with 1 changeover contact (SPDT)
- Enabling input of ON (work) or OFF (pause) interval
- Delay time for OFF (pause) interval, adjustable on front by rotary switch: 10...100%
- Delay time for ON (work) interval, adjustable on front by rotary switch: 10...100%
- Green LED indicator for power on
- Red LED indicator for relay state; flashing for delay
- Modular DIN 43880 housing, 1 module; suitable for fixing on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing
- IEC degree of protection: IP40 on front (only when mounted in housing or electric board with IP40); IP20 on terminals.

#### Certifications and compliance

Certifications obtained: UL Listed, for USA and Canada (cULus - File E93601) as Auxiliary Devices - Timers; EAC. Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n° 14.

### Off delay time relay. Multiscale. Multivoltage



TMD

Order code	Time of scale range	Rated auxiliary supply voltage [V]	Qty per pkg n°	Wt [kg]
<b>TMD</b>	0.06...0.6s 0.6...6s 6...60s 18...180s	24...240V AC/DC	1	0.080

#### General characteristics

- Electronic time relay, multiscale, multivoltage. True off delay; delay on break with start at relay de-energising
- 1 relay output with 1 changeover contact (SPDT)
- Delay time adjustable on front by rotary switch: 10...100%
- Green LED indicator for power on
- Modular DIN 43880 housing, 1 module; suitable for fixing on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing
- IEC degree of protection: IP40 on front (only when mounted in housing or electric board with IP40); IP20 on terminals.

#### Certifications and compliance

Certifications obtained: UL Listed, for USA and Canada (cULus - File E93601) as Auxiliary Devices - Timers; EAC, CCC. Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n° 14.



# 18 Time relays Modular version



## Time relay for starting. Multiscale. Multivoltage



TMST

Order code	Time of scale range	Rated auxiliary supply voltage [V]	Qty per pkg n°	Wt [kg]
<b>TMST</b>	0.1...1s 1...10s 6...60s 1...10min	24...48VDC 24...240VAC	1	0.090
<b>TMSTA440</b>	0.1...1s 1...10s 6...60s 1...10min	380...440VAC	1	0.090

### General characteristics

- Electronic time relay, multiscale, multivoltage for starting (star-delta, impedance, autotransformer, etc) of induction motors (squirrel cage), 2 separate timings
- 1 relay output with 2 normally open (N/O-SPST) contacts with common pole
- Delay time adjustable on front by rotary switch: 10-100% for star connection
- Starting and transition (20...300ms time scale - from star to delta), time adjustable on front by rotary switch
- Green LED indicator for power on
- Red LED indicator for relay state; flashing during delay and steady at delay lapsing
- Modular DIN 43880 housing, 1 module; suitable for fixing on 35mm DIN rail (IEC/EN/BS 60715) or screw fixing
- IEC degree of protection: IP40 on front (only when mounted in housing or electric board with IP40); IP20 on terminals.

### Certifications and compliance

Certifications obtained: UL Listed, for USA and Canada (cULus - File E93601) as Auxiliary Devices - Timers; EAC, CCC. Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n° 14.

## Time relay for staircase lighting with "zero crossing" load switching

new



TMLSL

Order code	Time of scale range	Rated auxiliary supply voltage [V]	Qty per pkg n°	Wt [kg]
<b>TMLSL</b>	0.5...20min	220...240VAC	1	0.090


### General characteristics

- Electronic time relay for staircase lighting single scale and single voltage
- 1 relay output with 1 powered normally open (N/O-SPST) contact
- Possible connections for 3- or 4-wire systems
- Zero crossing load switching
- Adjustable delay time on the front: 0.5...20min
- Selectable functions:
  - timed lighting + staircase cleaning
  - timed lighting with notice of shutdown + staircase cleaning
  - constant lighting
- Green LED for power presence signalling
- 1 control input can be connected to up to 50 light buttons (<1mA each)
- 1 relay output with normally open contact NO, 16A 250VAC
- LED lamp management up to 600W
- QR code for the direct connection to the LOVATO Electric website for the download of the technical manual
- Modular housing DIN 43880 (1 module), suitable for fixing on 35mm omega profile or screw fixing
- Degree of protection: IP40 on front (if mounted in container and/or electrical panel having IP40), IP20 on terminals.

### Certifications and compliance

Certifications obtained: EAC. Compliant with standards: IEC/EN/BS 61812-1, UL508, CSA C22.2 n°14.

### "ZERO CROSSING" LOAD SWITCHING - IDEAL FOR LED LAMPS



The time relay for staircase TMLSL uses "zero crossing" technology for load switching, which consists in monitoring the sinusoidal mains voltage and inserting the load at the exact instant in which the voltage passes through zero.

This has several advantages:

- reduction of the inrush current generated when the lamp is activated, which can reach very high values, especially in the increasingly popular LED lamps
- protection of the lamp and extension of the electrical life
- protection of the time relay contact from the risk of sticking
- reduction of consumption.



# 18 Time relays

Plug-in and flush mount version 48x48mm/1.9x1.9"  
Accessories

## Time relay



31L48TP...



31L48TPB...



31L48M...

## Accessories for 48x48mm/1.9x1.9" time relay



HR7XS1



31L48P8



HR7XS2



31L48P11



31L48AP

Order code	Time scale range	Rated auxiliary supply voltage	Qty per pkg	Wt
		[V]	n°	[kg]
Time relay on delay. Multiscale and multivoltage.				
<b>31L48TPS240</b>	0.3...780s	24VAC/DC 110VAC	1	0.124
<b>31L48TPM240</b>	18s...780min	220...240VAC	1	0.124
Time relay on delay. Multiscale and single voltage.				
<b>31L48TPBM24</b>	0.05s...10min	24VAC/DC	1	0.124
<b>31L48TPBM240</b>		220...240VAC	1	0.124
Time relay, multifunction, multivoltage and multiscale.				
<b>31L48MM240</b>	0.05s...10min	24...240V AC/DC	1	0.135
<b>31L48MH240</b>	0.05min...10h		1	0.135

Order code	Description	Qty per pkg	Wt
		n°	[kg]
<b>HR7XS1</b>	8-pin socket for screw fixing or on 35mm DIN rail (IEC/EN/BS 60715) of time relay type L48T....	10	0.061
<b>31L48P8</b>	8-pin socket for the door-mounting of time relay type 31L48T... with accessory 31L48AP. Screw terminals.	10	0.040
<b>HR7XS2</b>	11-pin socket for screw fixing or on 35mm DIN rail (IEC/EN/BS 60715) of time relay type 31L48M....	10	0.064
<b>31L48P11</b>	11-pin socket for the door-mounting of time relay type L48M... with accessory 31L48AP. Screw terminals.	10	0.048
<b>31L48AP</b>	Flush door mounting bracket	10	0.012

NOTE: max. conductor section for sockets: 2x2.5mm<sup>2</sup>/2x14AWG. Tightening torque: 0.8Nm/7.1lb.in.

## General characteristics

- TIME RELAY 31L48TP...
  - Electronic time relay, multiscale, multivoltage.
  - On delay, delay on make with start at relay energising
  - 1 relay output with 1 changeover contact (SPDT)
  - Delay time adjustable on front by rotary knob
  - Time range selected by dip switches:
    - 31L48TPS: 0.3...3s; 1.2...12s; 10...100s; 7.8...780s.
    - 31L48TPM: 18s...3min; 72s...12min; 10...100min; 78...780min
  - LED indicators for power on and relay state
  - Plug-in housing with 8-pin socket, HR7XS1 or 31L48P8 with accessory 31L48AP
  - Flush door-mounting bracket 31L48AP available
  - IEC protection degree: IP40 on front and IP20 at terminals.

## Time range setting

	A B	A B	A B	A B
	1 0	1 0	1 0	1 0
<b>31L48TPS</b>	0.3...3s	1.2...12s	10...100s	7.8...780s
<b>31L48TPM</b>	18s...3min	72s...12min	10...100min	78...780min

## TIME RELAY 31L48TPB...

- Electronic time relay, multiscale, single voltage, on delay function
- 2 relay outputs, each with 1 changeover contact (SPDT), configurable either delay on make or instantaneous
- Delay time adjustable on front by rotary knob
- Time range selected by dip switches:
  - 0.05...1s; 0.1...10s; 0.6s...1min; 6s...10min
- LED indicators for power on and relay state
- Plug-in housing with 8-pin socket, HR7XS1 or 31L48P8 with accessory 31L48AP
- Flush door-mounting bracket 31L48AP available
- IEC protection degree: IP40 on front and IP20 at terminals.

## Time range setting

	A B	A B	A B	A B
	1 0	1 0	1 0	1 0
<b>31L48TPB</b>	0.05...1s	0.1...10s	0.6s...1min	6s...10min

## TIME RELAY 31L48M...

- Electronic time relay, multiscale, multivoltage, multifunction
- Selectable functions: On delay, delay on make with start at relay energising. Pulse on relay energising with start on energising. Flasher, starting with OFF interval. Flasher, starting with ON interval. Time relay resetting is possible on closing of external contact (R) connected to terminals 7-6. Possible time relay stopping storing elapsed time on closing of external contact (M) connected to terminals 7-5 and then restarting time on its opening. See diagrams on page 18-9
- 2 relay outputs, each with 1 changeover contact; both delayed (SPDT)
- Delay time adjustable on front by rotary knob
- Time range selected by dip switches:
  - 31L48MM: 0.05...1s; 0.1...10s; 0.6s...1min; 6s...10min
  - 31L48MH: 0.05...1min; 0.1...10min; 0.6min...1h; 1min...10h
- LED indicators for power on and relay state
- Plug-in housing with 11-pin socket, HR7XS2 or 31L48P11 with accessory 31L48AP
- Flush door-mounting bracket 31L48AP available
- IEC protection degree: IP40 on front and IP20 at terminals.

## Time range setting

	A B	A B	A B	A B
	1 0	1 0	1 0	1 0
<b>31L48MM</b>	0.05...1s	0.1...10s	0.6s...1min	6s...10min
<b>31L48MH</b>	0.05...1min	0.1...10min	0.6min...1h	1min...10h

## SOCKETS HR7X... AND 31L48...

- 8-pin and 11-pin version
- Screw fixing or on DIN rail for HR7X..., flush mount for 31L48... with accessory 31L48AP
- Screw terminals
- Ratings: 10A - 250VAC.


## Certifications and compliance

Certifications obtained: cURus (for 31L48... and HR7X... type), CSA (for HR7X... type), EAC. Compliant with standards: IEC/EN/BS 61810 (for HR7X... type), IEC/EN/BS 61812-1, UL508, CSA C22.2 n° 14.


# 18 Time relays

Dimensions [mm (in)]  
Wiring diagrams

## TIME RELAYS




## 31L48...




## ACCESSORIES - SOCKETS


### HR7XS1




### HR7XS2



### 31L48P8





### 31L48P11



## Wiring diagrams



### TMP

On delay. Delay on make, with start at relay energising





### TMPA440

On delay. Delay on make, with start at relay energising




### TMM1


On delay. Delay on make, with start at relay energising




Pulse on relay energising with start at external contact closing




Pulse on relay energising with start on energising




Pulse on relay energising with start at external contact opening




Flasher, starting with OFF (pause) interval. Equal timing recycle




On-Off delay. Delay on make, with start at external contact closing, and delay at break, with start at external contact opening




Flasher, starting with ON (work) interval. Equal timing recycle




Internal ON/OFF trigger. Relay contact either closes or opens at each external contact closing



Off delay. Relay energising at external contact closing with start on break




Pulse generator. Unequal timing recycle, starting with OFF pulse time and 0.5sec ON time



### TMM1NFC

For operational diagrams see instruction manual I562 on the website [www.LovatoElectric.com](http://www.LovatoElectric.com), section download/technical instruction.















































# 18 Time relays

## Wiring diagrams



### TMM2









# 18 Time relays

## Wiring diagrams

### TMPL




Flasher, starting with ON interval.  
Equal timing recycle, ON first




W = Work (ON)  
P = Pause (OFF)

Flasher, starting with OFF interval.  
Equal timing recycle, OFF first




W = Work (ON)  
P = Pause (OFF)

### TMD





True off delay. Delay on break, starting at relay de-energising




### TMST

For starting




### TMLS


4-wire connection




3-wire connection




Timed lighting + staircase cleaning



Timed lighting with shutdown notice + staircase cleaning




Constant lighting




# 18 Time relays

## Wiring diagrams


### 31L48TP...





On delay




### 31L48TPB...




On delay with both instantaneous c/o contacts



On delay with one instantaneous c/o contact and one late-break c/o contact




### 31L48M...




T (preset time) = T1+T2  
 ● Contacts "M" and "R" are to be voltage free (dry).


On delay




Pulse on relay energising with start on energising



Flasher starting with OFF



Flasher starting with ON





# 18 Time relays

Technical characteristics  
Modular version



TYPE	TMP	TMPA440	TMM1 - TMM2	TMM1NFC	TMPL	TMD	TMST	TMLS
<b>DESCRIPTION</b>								
	On delay	On delay	Programmable multifunction	Programmable multifunction with NFC	Asymmetrical recycle	True off delay	For starting	Staircase illumination
	Multiscale	Multiscale	Multiscale	Multiscale	Multiscale	Multiscale	Multiscale	Single scale
	Multivoltage	Single voltage	Multivoltage	Multivoltage	Multivoltage	Multivoltage	Multivoltage	Single voltage
<b>CONTROL CIRCUIT</b>								
Rated auxiliary supply voltage Us	24...48VDC 24...240VAC	380...440VAC	12...240VAC/DC			24...240VAC/DC	24...48VDC 24...240VAC 380...440VAC	220...240VAC
Rated frequency	50/60Hz							
Operating voltage range	0.85...1.1Us							
Power consumption (maximum)	1.2VA/0.8W max (24...48VAC/DC) 16VA/0.9W max (110...240VAC)	19VA/1.7W max	TM M1: 0.6VA/0.3W max (12...48VAC/DC) 1.6VA/1.2W max (110...240VAC/DC) TM M2: 1.1VA/0.8W max (12...48VAC/DC) 1.8VA/1.2W max (110...240VAC/DC)	0.6VA/0.3W max (12...48VAC/DC) 1.6VA/1.2W max (110...240VAC/DC)	0.6VA/0.3W max (12...48VAC/DC) 1.6VA/1.2W max (110...240VAC/DC)	0.1VA/0.1W (24...48VAC/DC) 1.1VA/0.8W (110...240VAC/DC)	1.2VA/0.8W max (24...48VAC/DC) 1.6VA/0.9W max (110...240VAC/DC)	⊕
<b>TIMING CIRCUIT</b>								
Time setting range	Multiscale 0.1...1s 1...10s 6s...60s 1...10min 6min...1h 1...10h 0.1...1day 1...10days ON only OFF only	Multiscale 0.1...1s 1...10s 6s...60s 1...10min	Multiscale 0.1...1s 1...10s 6s...60s 1...10min 6min...1h 1...10h 0.1...1day 1...10days ON only OFF only	Multiscale 0.1s...999h programmable via NFC and APP	Multiscale 0.1...1s 1...10s 6s...60s 1...10min 6min...1h 1h...10h 0.1...1gg 1...10gg 3...30gg 10...100gg	Multiscale 0.06...0.6s 0.6...6s 6s...60s 18s...180s	Multiscale 0.1...1s 1...10s 6s...60s 1...10min	Single scale 0.5...20min
Setting accuracy	< ±9%		0		< ±9%		⊕	
Repeat accuracy	< ±0.1%	< ±0.5%	< ±0.5% - < ±0.2%	< ±0.1%	< ±0.2%	< ±0.5%		⊕
Influence of voltage variation	< ±0.01%						⊕	
Average variation of set delays related to +20°C condition	< ±0.2%						⊕	
Minimum power time	—	—	—	—	—	≥ 200ms	—	—
Minimum ON time	—	—	25ms (no maximum limit)			—	—	≥ 60ms (no max lim.)
Resetting time	during timing ≥ 100ms	≥ 100ms	≥ 100ms	≥ 100ms	≥ 100ms	—	≥ 100ms	⊕
	elapsed time ≥ 50ms	≥ 50ms	≥ 50ms	≥ 50ms	≥ 50ms	—	≥ 50ms	—
Immunity time for microbreakings	≤ 50ms	—	≤ 25ms - ≤ 15ms	≤ 25ms	≤ 25ms	—	≤ 40ms⊕	⊕
<b>RELAY OUTPUTS</b>								
Contact arrangement	1 delayed changeover	2 delayed changeover	TMM1: 1 delayed changeover TM M2: 1 inst./delayed N/O + 1 delayed c/o	1 delayed changeover	1 delayed changeover	1 delayed changeover	2 delayed N/O	1 delayed N/O
Maximum switching voltage	250VAC							
IEC conventional free air thermal current (Ith)	8A	8A	8A	8A	8A	5A	8A	16A
UL/CSA designation	B300							—
Electrical life (with rated load)	10 <sup>5</sup> cycles							
Mechanical life	30x10 <sup>6</sup> cycles							
Tightening torque maximum	max. 0.8Nm (7lb.in; 7...9lb.in per UL)							
Conductor section min-max	0.2...4mm <sup>2</sup> (24...12AWG; 12...18AWG per UL)							
<b>INSULATION (input-output)</b>								
IEC rated insulation voltage	250V							
IEC rated impulse withstand voltage	4kV							
IEC power frequency withstand voltage	2kV							
<b>AMBIENT CONDITIONS</b>								
Operating temperature	-20...+60°C							
Storage temperature	-30...+80°C							
Housing material	Self-extinguishing polyamide							

⊕ For 380...440VAC types: 19VA/1.7W max. ⊕ Used at 24...48VDC or 24...240VAC; ≤30ms at 380...440VAC. ⊕ Consult Technical support for information; see contact details on front cover.  
NOTE: N/O = normally open / SPST c/o = changeover / SPDT; inst. = instantaneous.

# 18 Time relays

Technical characteristics  
Plug-in and flush mount version 48x48mm/1.9x1.9"

TYPE	31L48TP...	31L48TPB...	31L48M...
<b>DESCRIPTION</b>			
	On delay	On delay	Programmable multifunction
	Multiscale	Multiscale	Multiscale
	Multivoltage	Single voltage	Multivoltage
<b>CONTROL CIRCUIT</b>			
Rated supply voltage $U_s$	24VAC/DC❶	24VAC/DC❶	24...240VAC/DC❶
	110VAC❶	220...240VAC❶	
	220...240VAC❶		
Rated frequency		50...60Hz	
Operating voltage range		0.85...1.1 $U_s$	
Power consumption (maximum)		6VA	
<b>TIMING CIRCUIT</b>			
Time setting range	31L48TPS... Multiscale 0.3...3s 1.2...12s 10...100s 7.8...780s	Multiscale 0.05...1s 0.10...10s 0.6s...1min 6s...10min	31L48MM... Multiscale 0.05...1s 0.1...10s 0.6s...1min 6s...10min
	31L48TPM... 18s...3min 72s...12min 10...100min 78...780min		31L48MH... 0.05...1min 0.1...10min 0.6min...1h 1min...10h
Setting accuracy		±5%	
Repeat accuracy		±0.5%	
Influence of voltage variation		±0.5%	
Average variation of set delays in related to 20°C condition	at -10°C	+2%	
	at +60°C	-3%	
Minimum ON time		—	
Resetting time	during operation	≥ 0.1s	≥ 0.1s
	elapsed time	≥ 65ms	≥ 65ms
Immunity time for microbreakings	≤ 40ms	≤ 40ms	≤ 40ms
<b>RELAY OUTPUTS</b>			
Number of relays	1	2	2
Contact arrangement	1 delayed c/o	2 del. or 1 inst. + 1 del. c/o	2 delayed c/o
Maximum switching voltage		250V	
IEC conventional free air thermal current (I <sub>th</sub> )		5A	
UL/CSA designation		B300	
Electrical life (with rated load)		10 <sup>5</sup> cycles	
Mechanical life		30x10 <sup>6</sup> cycles	
<b>CONNECTIONS</b>			
Tightening torque maximum		—	
Conductor section (min-max)		—	
<b>INSULATION (input-output)</b>			
IEC rated insulation voltage $U_i$		250V	
IEC power frequency withstand voltage $U_{imp}$		—	
IEC power frequency withstand voltage		2kV	
<b>AMBIENT CONDITIONS</b>			
Operating temperature		-10...+60°C	
Storage temperature		-30...+80°C	
Housing material		Self-extinguishing polyamide	

❶ Other voltages on request.  
NOTE: del. = delayed inst. = instantaneous c/o = changeover/SPDT